

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
9 June 2005 (09.06.2005)

PCT

(10) International Publication Number
WO 2005/053267 A1

(51) International Patent Classification⁷: H04L 29/06, 12/28, 9/32

(74) Agents: HIGGIN, Paul et al.; Swindell & Pearson, 48 Friar Gate, Derby DE1 1GY (GB).

(21) International Application Number: PCT/IB2003/006378

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(22) International Filing Date: 20 November 2003 (20.11.2003)

(84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): NOKIA CORPORATION [FI/FI]; Keilalahdentie 4, FIN-02150 Espoo (FI).

(72) Inventors; and


(75) Inventors/Applicants (for US only): KRUMMEL, Holger [DE/DE]; Knuwerweg 31, 44789 Bochum (DE). HARTWIG, Stephan [DE/DE]; Ernst Barlach Str. 13, 45276 Essen (DE).

Published:

— with international search report

[Continued on next page]

(54) Title: A METHOD AND DEVICE RELATING TO SECURITY IN A RADIO COMMUNICATIONS NETWORK



(57) Abstract: A method of joining a first device to a radio communications network controlled by a second device without contemporaneous user input of a secret at the second device, comprising: storing in the second device a secret generated at the second device; making the stored secret available in the first device; and creating in the first device and in the second device, using the secret, a secret key for use in securing communication between the first and second devices.

WO 2005/053267 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.